

## finish schedule

### CEILING FINISHES:

SYMBOL	MANUFACTURER	NUMBER/SERIES	COLOR	DESCRIPTION / NOTES
CF-01	ARMSTRONG	#673 KITCHEN ZONE	WHITE	24" X24" X 5/8" NON-PERFORATED VINYL-FACED LAY-IN CEILING TILES GRID: XL7326 PRELUDE XL 15/16"
CF-02	SHERWIN WILLIAMS	SW 7004	COLOR: SNOWBOUND FINISH: MATTE	ACRYLIC DRY FALL PAINT:DINING AREA
CF-03	SHERWIN WILLIAMS	SW 7015	COLOR: REPOSE GRAY FINISH: SATIN	RESTROOMS & RR CORRIDOR

## keyed notes

- CEILING BY CANOPY VENDOR; LIGHTING, FANS AND UNIT HEATERS INSTALLED BY E.C.
- COOLER / FREEZER CEILING BY WALK IN VENDOR, REFER TO SPECIFICATIONS BY IMPERIAL BROWN.
- OPEN TO DECK ABOVE COOLER.
- CEILING ELEMENT BY DECOR VENDOR, INSTALLED BY G.C.
- EXHAUST HOODS, REFER TO MECHANICAL DRAWINGS.
- SUPPLY & RETURN AIR DIFFUSERS, REFER TO MECHANICAL DRAWINGS.
- EXHAUST FAN, REFER TO MECHANICAL DRAWINGS.
- OMITTED
- SUPPLY AIR DUCTWORK AND DIFFUSERS- PAINT TO MATCH CEILING CF-02.
- LED STRIP FIXTURE - LOCATED BEHIND WINDOWS REFER TO WALL SECTION 01/A3.06.
- RECESSED LED TRIP FIXTURES MOUNTED BEHIND ACRYLIC & METAL MESH PANELS - REFER TO DETAIL 07/A4.2.
- REFER TO SUSPENSION CEILING DETAILS 02/A4.2.
- REFER TO TRACK MOUNTING DETAIL 01/A4.2.
- CEILING HEATER FOR DRIVE THRU WINDOW REFER TO MECHANICAL & ELECTRICAL SHEETS.
- WALKWAY & VESTIBULE CEILING BY G.C., COORDINATE CONNECTION TO CANOPY WITH VENDOR.

## lighting schedule

DESIGNATION	SYMBOL	DESCRIPTION
L8		6" RECESSED CAN LIGHT W/LED LAMP
L10		6"-6" & 5"-0" LONG SURFACE MOUNTED LED STRIP
L11		5" LONG RECESSED LED STRIP LIGHT
L13P		LED TRACK HEAD
L13 OMITTED		
L16		2' X' LED PANEL LIGHT
L18		6" RECESSED LED CAN - LOW PROFILE
L19		2X4 LED SUSPENDED PANEL LIGHT
L20		2X2 LED SUSPENDED PANEL LIGHT
L38		INCADESCENT STRING LIGHT
L39		4" LONG SUSPENDED LED STRIP LIGHT
L40		WALL MOUNT INCANDESCENT GLOBE LIGHT
W		WALL MOUNTED NIGHT LIGHT
EM		EXTERIOR EMERGENCY FIXTURE
EX		LED EMERGENCY/EXIT COMBO
CF		SURFACE MOUNTED CEILING FAN, REFER TO ELECTRICAL DRAWINGS
UH-1		CEILING MOUNTED ECLECTRIC HEATER, REFER TO MECHANICAL DRAWINGS

NOTE: SEE ELECTRICAL DRAWINGS AND SCHEDULES SHEET E302 FOR ADDITIONAL INFORMATION. LIGHTING PACKAGE PROCURED FROM STANDARD ELECTRIC NATIONAL ACCOUNTS 978-404-1333, ATTN. RYAN HUNT rhunt@standardelectric.com

## general notes

### LIGHTING FIXTURES

- ALL LIGHTING FIXTURES SHALL BE POSITIVELY ATTACHED TO THE SUSP. CEILING SYSTEM. THE ATTACHMENT DEVICE SHALL HAVE A CAPACITY OF 100 % OF THE LIGHTING FIXTURE WEIGHT ACTING IN ANY DIRECTION No.12 GA. HANGERS SHALL BE ATTACHED TO THE GRID MEMBERS WITHIN 3" OF EACH CORNER OF EACH FIXTURE. TANDEM FIXTURES MAY UTILIZE COMMON WIRES.
- LIGHTING FIXTURE WEIGHING LESS THAN 56 LBS. SHALL HAVE, IN ADDITION TO THE REQUIREMENTS OUTLINED ABOVE, TWO No.12 GA. HANGERS CONNECTED FROM THE FIXTURE HOUSING TO THE STRUCTURE ABOVE, THESE WIRES MAY BE SLACK.
- LIGHTING FIXTURES 56 LBS. OR MORE SHALL BE SUPPORTED DIRECTLY FROM THE STRUCTURE ABOVE BY APPROVED HANGERS.
- PENDANT-HUNG LIGHTING FIXTURES SHALL BE SUPPORTED DIRECTLY FROM THE STRUCTURE ABOVE USING No. 9 GA. WIRE OR APPROVED ALTERNATE SUPPORT WITHOUT USING THE CEILING SUSPENSION SYSTEM FOR DIRECT SUPPORT.
- LOUVERS, AND PANEL FRONTS SHALL BE SPRAY PAINTED TO MATCH ADJACENT SURFACES, INCLUDING FACTORY FINISHED ITEMS. NO BRUSH PAINTING OF THESE ITEMS WILL BE PERMITTED.
- ALL EXPOSED GYPSUM BOARD SHALL BE SEALED WITH ONE COAT OF SEALER AND FOLLOWED BY TWO COATS OF SPECIFIED FINISH. (RE: SPECS.)
- FOR DETAILS NOT CALLED OUT ON REFLECTED CEILING PLAN, SEE INTERIOR ROOM ELEVATIONS.
- PLACEMENT OF SPEAKERS AND AUDIO EQUIPMENT TO BE BY MUSIC CO.
- CEILING HEIGHTS SHOWN ARE FROM FINISHED CEILING SURFACE TO CONCRETE SLAB.
- LOCATE ALL LIGHTS AND CEILING REGISTERS AS SHOWN
- REFER TO MECH. DRAWINGS FOR ALL REGISTERS AND DIFFUSERS.
- REFER TO ELEC. DRAWINGS FOR ALL LIGHTING FIXTURES.

